

- Remove the TLS Key Pair belonging to the passed in *CCDID*.

14.5. TLS Client Management Cluster

This Cluster is used to provision TLS Endpoints with enough information to facilitate subsequent connection.

Commands in this cluster uniformly use the [Large Message](#) qualifier, even when the command doesn't require it, to reduce the testing matrix.

This cluster SHALL be present on the [root node endpoint](#) when required by a device type, MAY be present on that endpoint otherwise, and SHALL NOT be present on any other Endpoint of any Node.

14.5.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial Release

14.5.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Utility	Node	TLSCIENT

14.5.3. Cluster ID

ID	Name
0x0802	TLS Client Management

14.5.4. Data Types

14.5.4.1. TLSEndpointID Type

This data type is derived from uint16 and represents a provisioned endpoint with valid values from 0 to 65534. This value SHOULD start at 0 and monotonically increase by 1 with each new allocation provisioned by the Node. A value incremented past 65534 SHOULD wrap to 0. The Node SHALL verify that a new value does not match any other value for this type. If such a match is found, the value SHALL be changed until a unique value is found.

14.5.4.2. TLSEndpointStruct Type

This struct encodes details about a TLS Endpoint.