

For end of container element type the tag control bits are set to 0. Any other combination of the tag control bits for this element type only is reserved. See [Section A.10, “End of Container Encoding”](#).

A.7.2. Tag Control Field

The tag control field identifies the form of tag assigned to the element (including none) as well as the encoding of the tag octets.

Control Octet								Description
Tag Control			Element Type					
7	6	5	4	3	2	1	0	
0	0	0	x	x	x	x	x	Anonymous Tag Form, 0 octets
0	0	1	x	x	x	x	x	Context-specific Tag Form, 1 octet
0	1	0	x	x	x	x	x	Common Profile Tag Form, 2 octets
0	1	1	x	x	x	x	x	Common Profile Tag Form, 4 octets
1	0	0	x	x	x	x	x	Implicit Profile Tag Form, 2 octets
1	0	1	x	x	x	x	x	Implicit Profile Tag Form, 4 octets
1	1	0	x	x	x	x	x	Fully-qualified Tag Form, 6 octets
1	1	1	x	x	x	x	x	Fully-qualified Tag Form, 8 octets

A.8. Tag Encoding

Tags are encoded in 0, 1, 2, 4, 6 or 8 octet widths as specified by the tag control field. Tags consist of up to three numeric fields: a *Vendor ID field*, a *profile number field*, and a *tag number field*. All fields are encoded in little-endian order. The tag fields are ordered as follows:

Vendor ID	Profile Number	Tag Number
0 or 2 octets	0 or 2 octets	1, 2, or 4 octets

A.8.1. Fully-Qualified Tag Form

A profile-specific tag can be encoded in *fully-qualified tag form*, where the encoding includes all three tag components (Vendor ID, profile number and tag number). Two variants of this form are supported, one with a 16-bit tag number and one with a 32-bit tag number. The 16-bit variant SHALL be used with tag numbers < 65536, while the 32-bit variant SHALL be used with tag numbers >= 65536.

Tag Control	Vendor ID Size	Profile Number Size	Tag Number Size	
110b	2 octets	2 octets	2 octets	For tag numbers < 65536