

B.2.3. Namespace Definition (namespace-def)

Namespace Definition Syntax

```
namespace ns-name { ns-scoped-defs }
```

ns-name:

name

scoped-name

ns-scoped-defs:

ns-scoped-def

ns-scoped-defs, ns-scoped-def

ns-scoped-def:

type-def

field-group-def

protocol-def

namespace-def

namespace introduces a new naming scope. Definitions that appear within the braces of a namespace definition are scoped to that namespace, such that their names need only be unique within the bounds of the enclosing scope. The namespace scoped definitions SHALL be separated by commas.

In general, four forms of definitions MAY appear within a namespace: type definitions ([type-def](#)), **FIELD GROUP** definitions ([field-group-def](#)), protocol definitions ([protocol-def](#)) and further namespace definitions ([namespace-def](#)). Namespace definitions MAY be nested to any level. Protocol definitions, however, are restricted such that they SHALL NOT be nested. Thus a namespace can only contain a protocol definition if the namespace itself is not located, at any level, within another protocol definition.

The name used in a namespace definition MAY be either a simple **name**, such as **a**, or a **scoped-name**, such as **a.b.c**. When a **scoped-name** is used, the effect is exactly as if multiple nested namespaces had been declared, each named after a part of the scoped name.

It is legal to have multiple namespace definitions, each with the same name, defined within the same scope. The effect is as if there were only a single namespace definition containing a union of the enclosed definitions. Thus, a namespace definition with the same name as a preceding definition MAY be seen as a kind of continuation of the earlier one.

Namespace Definition Examples

```
namespace abc
{
    property => FLOAT32 [ range 0..50 ],
```