

Both the name and id value used in a **VENDOR** definition SHALL be unique across all such definitions. However, for convenience, a **VENDOR** definition MAY be repeated provided that the name and id are the same.

The Matter vendor (0x00000) is implicitly defined in all schemas, although it MAY be explicitly defined as well:

VENDOR Definition Example

```
Matter => VENDOR [ 0x0000 ]
```

B.3. Types

The TLV format supports 10 fundamental types: integers (signed and unsigned), floats, booleans, UTF-8 strings, octet strings, structures, arrays, lists and nulls. Accordingly, a TLV Schema MAY use one of the following type constructs to constrain an encoding to be one of these fundamental types.

B.3.1. ARRAY / ARRAY OF

ARRAY Syntax

```

ARRAY [ qualifier ] OF type-or-ref           // uniform array
ARRAY [ qualifier ] { type-pattern }         // pattern array

qualifier (optional):
    length
    nullable

type-pattern:
    type-pattern-item
    type-pattern, type-pattern-item

type-pattern-item:
    type-or-ref quantifier                   // unnamed item
    identifier : type-or-ref quantifier      // named item

quantifier (optional):
    *                                       // zero or more
    +                                       // one or more
    { count }                             // exactly count
    { min..max }                           // between min and max
    { min.. }                               // at least min

```

ARRAY and **ARRAY OF** declare an element that is encoded as a TLV [Array](#).