

```

weather-tuple => ARRAY
{
    timestamp          : UNSIGNED INTEGER [ range 32-bits ],
    temperature        : FLOAT64,
    relative-humidity  : UNSIGNED INTEGER [ range 0..100 ],
    precipitation       : UNSIGNED INTEGER [ range 0..100 ],
}

named-vector => ARRAY
{
    name                : STRING,
                      FLOAT64 *,
}

```

B.3.2. BOOLEAN

BOOLEAN Syntax

```

BOOLEAN [ qualifier ]

qualifier (optional):
    nullable

```

BOOLEAN declares an element that SHALL be encoded as a TLV **Boolean**.

If the **nullable** qualifier is given, a TLV **Null** MAY be encoded in its place.

BOOLEAN Example

```

pathlight-enabled => BOOLEAN

```

B.3.3. FLOAT32 / FLOAT64

FLOAT Syntax

```

FLOAT32 [ qualifier ]
FLOAT64 [ qualifier ]

qualifier (optional):
    range
    nullable

```

FLOAT32 declares an element that SHALL be encoded as a TLV **floating point number** with the **element type** indicating a 4-octet **IEEE 754-2019** single-precision value. Correspondingly, **FLOAT64** declares a TLV element that SHALL be encoded as a TLV **floating point number** with the **element**