

A **nullable** qualifier MAY be used to indicate that a TLV **Null** MAY be encoded in place of the **LIST** or **LIST OF**. Note that a list that has been replaced by a Null is distinct (in terms of its encoding) from a list that has no items.

B.3.5.1. Item Names

As with the **ARRAY** type, items or groups of items in a pattern list MAY be given textual names to distinguish their purposes. Item names within a pattern list SHALL be unique.

B.3.5.2. Item Tags

Items within a pattern list can have a **tag** qualifier that specifies a particular tag value that SHALL be encoded with the item. The specific tag can be protocol-specific or context-specific, or the **anonymous** tag. The assigned tag values are not required to be unique among the items in a pattern list.

When no explicit tag qualifier is given (which is always the case for uniform lists) the items in a list automatically assume the default tag of their underlying types, if such a tag is provided. This can occur in two situations: 1) when the underlying type is a reference to a type definition that declares a default tag, and 2) when the underlying type is a **CHOICE OF** whose alternates declare default tags. See [default tag](#) for further information.

If no tag qualifier is given, and no default tag is available, an encoder is allowed to encode list items with any tag of their choosing.

B.3.6. OCTET STRING

OCTET STRING Syntax

```
OCTET STRING [ qualifier ]
```

qualifier (optional):

[length](#)
[nullable](#)

OCTET STRING declares an element that is encoded as a TLV **Octet String**, and in particular with the **element type** indicating it's an Octet String.

The minimum and maximum number of bytes can be constrained using the [length](#) qualifier.

OCTET STRING Example

```
address => OCTET STRING [ length 8 ]
```

B.3.7. NULL

NULL Syntax

```
NULL
```