

```
===== Decryption algorithm outputs =====
-> Received counter: 0b:00:00:00
-> Application data : 'This is a longer'
-> Invalid Check-In message - Received counter has already been used
```

Test 5

This test only had decryption processing because it tests the nonce validation that only applies to the decryption process.

```
===== Decryption algorithm inputs =====
-> Check-in message payload :
f9:34:67:6e:a6:e0:70:7b:7a:d7:81:4f:f8:2e:5b:18:d1:9a:23:b2:e4:fa:df:82:92:53:51:7f:f3
:c9:1d:8d:47:84:31:5a:1e:32:08:b8:ec:f6:11:8b:02:1a:5a:4c:d4:e9:d4:13:8d:ff:29:71
-> Symmetric Key: ca:67:d4:1f:f7:11:29:10:fd:d1:8a:1b:f9:9e:a9:74
-> Client counter: 0b:00:00:00

===== Decryption algorithm outputs =====
-> Failed to decrypt Check-In message.
```

Test 6

This test only had decryption processing because it tests the nonce validation that only applies to the decryption process.

```
===== Decryption algorithm inputs =====
-> Check-in message payload :
06:34:67:6e:a6:e0:70:7b:7a:d7:81:4f:f8:29:5b:18:d1:9a:23:b2:e4:fa:df:82:92:53:51:7f:f3
:c9:1d:8d:47:84:2e:41:02:3c:03:ad:66:ac:4d:ca:72:47:e0:e4:c6:6b:d9:d3:99:13:e2:3d:82:3
2:b9:61:fa:92:26
-> Symmetric Key: ca:67:d4:1f:f7:11:29:10:fd:d1:8a:1b:f9:9e:a9:74
-> Client counter: 0f:00:00:00

===== Decryption algorithm outputs =====
-> Received counter: 0b:00:00:00
-> Application data : 'This is a longer longer string'
-> Invalid Check-In message - Nonce and received counter do not match.
```

F.5. Fabric Table Vendor ID Verification Procedure Test Vector

This subsection contains a worked example of the [Fabric Table Vendor ID Verification Procedure](#).

All key pairs used are examples, not to be reused in implementations.