

1.2.6.2.2. EffectVariant Field

This field SHALL indicate which variant of the effect, indicated in the EffectIdentifier field, SHOULD be triggered. If a device does not support the given variant, it SHALL use the default variant. This field SHALL contain one of the values in [EffectVariantEnum](#).

1.2.6.2.3. Effect on Receipt

On receipt of this command, the device SHALL execute the trigger effect indicated in the EffectIdentifier and EffectVariant fields. If the EffectVariant field specifies a variant that is not supported on the device, it SHALL execute the default variant.

1.3. Groups Cluster

The Groups cluster manages, per endpoint, the content of the node-wide Group Table that is part of the underlying interaction layer.

In a network supporting fabrics, group IDs referenced by attributes or other elements of this cluster are scoped to the accessing fabric.

The Groups cluster is scoped to the endpoint. Groups cluster commands support discovering the endpoint membership in a group, adding the endpoint to a group, removing the endpoint from a group, removing endpoint membership from all groups. All commands defined in this cluster SHALL only affect groups scoped to the accessing fabric.

When group names are supported, the server stores a name string, which is set by the client for each assigned group and indicated in response to a client request.

Note that configuration of group addresses for outgoing commands is achieved using the Message Layer mechanisms where the Group Table is not involved. Hence this cluster does not play a part in that.

1.3.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Mandatory global ClusterRevision attribute added; CCB 1745 2100
2	CCB 2289
3	CCB 2310 2704
4	New data model format and notation

1.3.2. Classification