

| ID | Name           | Type     | Constraint | Quality | Fallback | Conformance |
|----|----------------|----------|------------|---------|----------|-------------|
| 0  | <b>GroupID</b> | group-id | min 1      |         |          | M           |

#### 1.3.7.4.1. Effect on Receipt

On receipt of the RemoveGroup command, the server SHALL perform the following procedure:

1. If the command fields are not within constraints, the status SHALL be CONSTRAINT\_ERROR and the server continues from step 4.
2. If the server endpoint is a member of the group indicated by the GroupID, the server SHALL remove the server endpoint membership in the group, the status SHALL be SUCCESS, and the server continues from step 4.
3. Else the status SHALL be NOT\_FOUND.
4. If the RemoveGroup command was received as a unicast, the server SHALL generate a RemoveGroupResponse command with the Status field set to the evaluated status. If the RemoveGroup command was received as a groupcast, the server SHALL NOT generate a RemoveGroupResponse command.

See [RemoveGroupResponse](#) for a description of the response command.

Additionally, if the Scenes Management cluster is supported on the same endpoint, scenes associated with the indicated group SHALL be removed on that endpoint.

#### 1.3.7.5. RemoveAllGroups Command

The RemoveAllGroups command allows a client to direct the server to remove all group associations for the server endpoint.

##### 1.3.7.5.1. Effect on Receipt

On receipt of this command, the server SHALL remove all group memberships for the server endpoint from the Group Table. If the RemoveAllGroups command was received as unicast and a response is not suppressed, the server SHALL generate a response with the Status field set to SUCCESS.

Additionally, if the Scenes Management cluster is supported on the same endpoint, all scenes, except for scenes associated with group ID 0, SHALL be removed on that endpoint.

#### 1.3.7.6. AddGroupIfIdentifying Command

The AddGroupIfIdentifying command allows a client to add group membership in a particular group for the server endpoint, on condition that the endpoint is identifying itself. Identifying functionality is controlled using the Identify cluster, (see [Identify Cluster](#)).

For correct operation of the AddGroupIfIdentifying command, any endpoint that supports the Groups server cluster SHALL also support the Identify server cluster.

This command might be used to assist configuring group membership in the absence of a commis-