

sioning tool.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupID	group-id	min 1			M
1	GroupName	string	max 16			M

1.3.7.6.1. GroupID Field

This field SHALL be used to identify the group and any associated key material to which the server endpoint is to be added.

1.3.7.6.2. GroupName Field

This field MAY be set to a human-readable name for the group. If the client has no name for the group, the GroupName field SHALL be set to the empty string.

Support of group names is optional and is indicated by the FeatureMap and NameSupport attribute.

1.3.7.6.3. Effect on Receipt

If the server does not support group names, the GroupName field SHALL be ignored.

On receipt of the AddGroupIfIdentifying command, the server SHALL perform the following procedure:

1. The server verifies that it is currently identifying itself. If the server is not currently identifying itself, the status SHALL be SUCCESS, and the server continues from step 7.
2. If the command fields are not within constraints, the status SHALL be CONSTRAINT_ERROR and the server continues from step 7.
3. If the receiving node requires security material to support the group ID, and that material does not exist for this group ID, the status SHALL be UNSUPPORTED_ACCESS and the server continues from step 7.
4. If the server endpoint is a member of the group indicated by the GroupID, the status SHALL be SUCCESS and the server continues from step 7.
5. If there are no available resources to add the membership for the server endpoint, the status SHALL be RESOURCE_EXHAUSTED and the server continues from step 7.
6. The server SHALL add the server endpoint as a member of the group indicated by the GroupID, the group name SHALL be updated (if supported) to GroupName, and the status SHALL be SUCCESS.
 - a. If the GroupID had already been added to the Group Table because of a previous AddGroup or AddGroupIfIdentifying command and a GroupName is provided and the server supports GroupName storage, then the GroupName associated with the GroupID in the Group Table SHALL be updated to reflect the new GroupName provided for the Group, such that subsequent ViewGroup commands yield the same name for all endpoints which have a group association to the given GroupID.