

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupID	group-id	all			M
1	SceneID	uint8	max 254			M

1.4.9.4.1. GroupID Field

This field SHALL indicate the group identifier in the Group Table.

1.4.9.4.2. SceneID Field

This field SHALL indicate the scene identifier in the Scene Table.

1.4.9.4.3. Effect on Receipt

On receipt of this command, the server SHALL perform the following procedure:

1. If the value of the GroupID field is non-zero, the server verifies that the endpoint has an entry for that GroupID in the Group Table. If there is no such entry in the Group Table, the status SHALL be INVALID_COMMAND and the server continues from step 4.
2. The server verifies that the scene entry corresponding to the GroupID and SceneID fields exists in its Scene Table. If there is no such entry in its Scene Table, the status SHALL be NOT_FOUND and the server continues from step 4.
3. The server retrieves the requested scene entry from its Scene Table and the status SHALL be SUCCESS.
4. If the ViewScene command was received as a unicast, the server SHALL then generate a ViewSceneResponse command with the retrieved scene entry and the Status field set to the evaluated status.

NOTE

The order of attributes within the ExtensionFieldSetStruct MAY differ in implementation-defined ways from any potential order given in a prior AddScene.

1.4.9.5. ViewSceneResponse Command

This command is sent in response to the [ViewScene](#) command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	status	desc			M
1	GroupID	group-id	all			M
2	SceneID	uint8	max 254			M
3	Transition-Time	uint32	max 60000000			Status == SUCCESS
4	SceneName	string	max 16			Status == SUCCESS