

1.4.9.6.3. Effect on Receipt

On receipt of this command, the server SHALL perform the following procedure:

1. If the value of the GroupID field is non-zero, the server verifies that the endpoint has an entry for that GroupID in the Group Table. If there is no such entry in the Group Table, the status SHALL be INVALID_COMMAND and the server continues from step 4.
2. The server verifies that the scene entry corresponding to the GroupID and SceneID fields exists in its Scene Table. If there is no such entry in its Scene Table, the status SHALL be NOT_FOUND and the server continues from step 4.
3. The server removes the requested scene entry from its Scene Table and the status SHALL be SUCCESS.
4. If the RemoveScene command was received as a unicast, the server SHALL then generate a RemoveSceneResponse command with the Status field set to the evaluated status.

1.4.9.7. RemoveSceneResponse Command

This command is sent in response to the [RemoveScene](#) command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	status	desc			M
1	GroupID	group-id	all			M
2	SceneID	uint8	max 254			M

1.4.9.7.1. Status Field

This field SHALL be set according to the Effect on Receipt section for [RemoveScene](#) command.

1.4.9.7.2. GroupID Field

The GroupID field SHALL be set to the corresponding field of the received [RemoveScene](#) command.

1.4.9.7.3. SceneID Field

The SceneID field SHALL be set to the corresponding field of the received [RemoveScene](#) command.

1.4.9.7.4. When Generated

This command is generated in response to a received [RemoveScene](#) command.

1.4.9.8. RemoveAllScenes Command

This command removes all scenes for the specified GroupID.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	GroupID	group-id	all			M