

1.10.8.4. LowNoise Tag

Either the mode is inherently low noise or the device optimizes for that.

1.10.8.5. LowEnergy Tag

The device is optimizing for lower energy usage in this mode. Sometimes called "Eco mode".

1.10.8.6. Vacation Tag

A mode suitable for use during vacations or other extended absences.

1.10.8.7. Min Tag

The mode uses the lowest available setting value.

1.10.8.8. Max Tag

The mode uses the highest available setting value.

1.10.8.9. Night Tag

The mode is recommended or suitable for use during night time.

1.10.8.10. Day Tag

The mode is recommended or suitable for use during day time.

1.11. Low Power Cluster

This cluster provides an interface for managing low power mode on a device.

This cluster would be supported on an endpoint that represents a physical device with a low power mode. This cluster provides a `sleep()` command to allow clients to manually put the device into low power mode. There is no command here to wake up a sleeping device because that operation often involves other protocols such as [Wake On LAN](#). Most devices automatically enter low power mode based upon inactivity.

The cluster server for Low Power is implemented by a device that supports a low power mode, such as a TV, Set-top box, or Smart Speaker.

NOTE

We have considered a "DisableLowPowerMode" command but have not added it due to suspected issues with energy consumption regulations. This can be added in the future.

1.11.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.