

The cluster server for Wake on LAN or Wake on WLAN is implemented by a device that supports the Wake on LAN/WLAN protocol, such as a TV, Set-top Box, or Smart Speaker.

1.12.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

1.12.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	WAKEONLAN

1.12.3. Cluster ID

ID	Name
0x0503	Wake on LAN

1.12.4. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	MACAddress	string	max 12	F		R V	O
0x0001	LinkLocalAddress	ipv6adr	desc	F		R V	O

1.12.4.1. MACAddress Attribute

This attribute SHALL indicate the current MAC address of the device. Only 48-bit MAC Addresses SHALL be used for this attribute as required by the Wake on LAN protocol.

Format of this attribute SHALL be an upper-case hex-encoded string representing the hex address, like **12345678ABCD**.

1.12.4.2. LinkLocalAddress Attribute

This attribute SHALL indicate the current link-local address of the device. Only 128-bit IPv6 link-local addresses SHALL be used for this attribute.

NOTE

Some companies may consider MAC Address to be protected data subject to PII handling considerations and will therefore choose not to include it or read it. The MAC Address can often be determined using ARP in IPv4 or NDP in IPv6.