

1.13. Switch Cluster

This cluster exposes interactions with a switch device, for the purpose of using those interactions by other devices.

Two types of switch devices are supported: latching switch (e.g. rocker switch) and momentary switch (e.g. push button), distinguished with their feature flags.

Interactions with the switch device are exposed as attributes (for the latching switch) and as events (for both types of switches).

An interested client MAY subscribe to these attributes/events and thus be informed of the interactions, and can perform actions based on this, for example by sending commands to perform an action such as controlling a light or a window shade.

1.13.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision
2	Behavior clarifications for ambiguous combinations of events; Introduction of TotalNumberOfPressesCounted == 0 when MultiPressMax is exceeded; Introduction of ActionSwitch feature flag.

1.13.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	SWTCH

1.13.3. Cluster ID

ID	Name
0x003B	Switch

1.13.4. Features

These feature flags SHALL be used to indicate the physics as well as the detection/reporting capabilities of the device represented by the cluster.

Bit	Code	Feature	Conformance	Summary
0	LS	LatchingSwitch	O.a	Switch is latching
1	MS	MomentarySwitch	O.a	Switch is momentary