



Figure 12. Switch device with joystick

Therefore, in the "joystick" variation, there could be a succession of InitialPress events without an intermediate ShortRelease events - unlike the "window blinds control" variation which will always have such an intermediate ShortRelease event.

1.14. Operational State Cluster

This cluster supports remotely monitoring and, where supported, changing the operational state of any device where a state machine is a part of the operation.

This cluster defines common states, scoped to this cluster (e.g. Stopped, Running, Paused, Error). A derived cluster specification may define more states scoped to the derivation. Manufacturer specific states are supported in this cluster and any derived clusters thereof. When defined in a derived instance, such states are scoped to the derivation.

Actual state transitions are dependent on both the implementation, and the requirements that may additionally be imposed by a derived cluster.

An implementation that supports remotely starting its operation can make use of this cluster’s Start command to do so. A device that supports remote pause or stop of its currently selected operation can similarly make use of this cluster’s Pause and Stop commands to do so. The ability to remotely pause or stop is independent of how the operation was started (for example, an operation started by using a manual button press can be stopped by using a Stop command if the device supports remotely stopping the operation).

Additionally, this cluster provides events for monitoring the operational state of the device.

1.14.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision