

Revision	Description
2	The Pause and Resume commands are usable in all compatible states. Define reserved ranges for base/derived clusters.
3	Changed CountdownTime attribute to Q quality.

1.14.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	OPSTATE

1.14.3. Cluster ID

ID	Name
0x0060	Operational State

1.14.4. Data Types

1.14.4.1. OperationalStateEnum Type

This type defines the set of known operational state values, and is derived from enum8. The following table defines the applicable ranges for values that are defined within this type. All values that are undefined SHALL be treated as reserved. As shown by the table, states that may be specific to a certain Device Type or other modality SHALL be defined in a derived cluster of this cluster.

Value	Name	Summary
0x00 to 0x3F	GeneralStates	Generally applicable values for state, defined herein
0x40 to 0x7F	DerivedClusterStates	Derived Cluster defined states
0x80 to 0xBF	ManufacturerStates	Vendor specific states

The derived cluster-specific state definitions SHALL NOT duplicate any general state definitions. That is, a derived cluster specification of this cluster cannot define states with the same semantics as the general states defined below.

A manufacturer-specific state definition SHALL NOT duplicate the general state definitions or derived cluster state definitions. That is, a manufacturer-defined state defined for this cluster or a derived cluster thereof cannot define a state with the same semantics as the general states defined below or states defined in a derived cluster. Such manufacturer-specific state definitions SHALL be scoped in the context of the Vendor ID present in the Basic Information cluster.

The following table defines the generally applicable states.