

ID	Name	Priority	Access	Conformance
0x01	OperationCompletion	INFO	V	O

1.14.7.1. OperationalError Event

This event is generated when a reportable error condition is detected. A device that generates this event SHALL also set the OperationalState attribute to Error, indicating an error condition.

This event SHALL contain the following fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ErrorState	ErrorStateStruct	all			M

1.14.7.2. OperationCompletion Event

This event SHOULD be generated when the overall operation ends, successfully or otherwise. For example, the completion of a cleaning operation in a Robot Vacuum Cleaner, or the completion of a wash cycle in a Washing Machine.

It is highly RECOMMENDED that appliances device types employing the Operational State cluster support this event, even if it is optional. This assists clients in executing automations or issuing notifications at critical points in the device operation cycles.

This event SHALL contain the following fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Completion-ErrorCode	enum8	all			M
1	TotalOperationalTime	elapsed-s	all	X		O
2	PausedTime	elapsed-s	all	X		O

1.14.7.2.1. CompletionErrorCode Field

This field provides an indication of the state at the end of the operation. This field SHALL have a value from the [ErrorStateEnum](#) set. A value of NoError indicates success, that is, no error has been detected.

1.14.7.2.2. TotalOperationalTime Field

The total operational time, in seconds, from when the operation was started via an initial Start command or autonomous/manual starting action, until the operation completed. This includes any time spent while paused. There may be cases whereby the total operational time exceeds the maximum