

1.15.5. Data Types

1.15.5.1. AlarmBitmap Type

This data type SHALL be a map32 with values defined by the derived cluster. The meaning of each bit position SHALL be consistent for all attributes in a derived cluster. That is, if bit 0 is defined for an alarm, the Latch, State, and Supported information for that alarm are also bit 0.

1.15.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	Mask	Alarm- Bitmap	all			R V	M
0x0001	Latch	Alarm- Bitmap	all	F		R V	RESET
0x0002	State	Alarm- Bitmap	all			R V	M
0x0003	Supported	Alarm- Bitmap	all	F		R V	M

1.15.6.1. Mask Attribute

This attribute SHALL indicate a bitmap where each bit set in the Mask attribute corresponds to an alarm that SHALL be enabled.

1.15.6.2. Latch Attribute

This attribute SHALL indicate a bitmap where each bit set in the Latch attribute SHALL indicate that the corresponding alarm will be latched when set, and will not reset to inactive when the underlying condition which caused the alarm is no longer present, and so requires an explicit reset using the Reset command.

1.15.6.3. State Attribute

This attribute SHALL indicate a bitmap where each bit SHALL represent the state of an alarm. The value of true means the alarm is active, otherwise the alarm is inactive.

1.15.6.4. Supported Attribute

This attribute SHALL indicate a bitmap where each bit SHALL represent whether or not an alarm is supported. The value of true means the alarm is supported, otherwise the alarm is not supported.

If an alarm is not supported, the corresponding bit in Mask, Latch, and State SHALL be false.

1.15.7. Commands