

1.16.4.3. ConfirmationReply Feature

This feature SHALL indicate that the device is capable of collecting a free-form text response to a message.

1.16.4.4. ProtectedMessages Feature

This feature SHALL indicate that the device is capable of requiring the user to authenticate before viewing a message; e.g. entering a PIN or password before viewing a message with billing information.

1.16.5. Data Types

1.16.5.1. MessageID Type

This data type is an octstr of fixed length 16, containing the binary encoding of a UUID as specified in [RFC 4122](#).

1.16.5.2. MessageControlBitmap Type

This data type is derived from map16, and indicates control information related to a message.

Bit	Name	Summary	Conformance
0	ConfirmationRequired	Message requires confirmation from user	CONF
1	ResponseRequired	Message requires response from user	RESP
2	ReplyMessage	Message supports reply message from user	RPLY
3	MessageConfirmed	Message has already been confirmed	CONF
4	MessageProtected	Message required PIN/password protection	PROT

1.16.5.2.1. ConfirmationRequired Bit

This bit SHALL indicate that the message originator requests a confirmation of receipt by the user. If confirmation is required, the device SHOULD present the message until it is either confirmed by the user selecting a confirmation option, or the message expires.

1.16.5.2.2. ResponseRequired Bit

This bit SHALL indicate that a [MessagePresented](#) event SHOULD be generated based on the response of the user to the message.