

Access Modifier: Fabric-Sensitive						
ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	MessageID	MessageID				M

1.16.8.1.1. MessageID Field

This field SHALL indicate the [MessageID](#) for newly added message.

1.16.8.2. MessagePresented Event

This event SHALL be generated when the message is presented to the user.

Access Modifier: Fabric-Sensitive						
ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	MessageID	MessageID				M

1.16.8.2.1. MessageID Field

This field SHALL indicate the [MessageID](#) for the message being presented.

1.16.8.3. MessageComplete Event

This event SHALL be generated when the message is confirmed by the user, or when the [Duration](#) field of the message has elapsed without confirmation.

Access Modifier: Fabric-Sensitive						
ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	MessageID	MessageID				M
1	ResponseID	uint32	all	X		RESP
2	Reply	string	max 256	X		RPLY
3	FutureMessagesPreference	FutureMessagePreferenceEnum	all	X		M

1.16.8.3.1. MessageID Field

This field SHALL indicate the [MessageID](#) for the message being confirmed.

1.16.8.3.2. ResponseID Field

This field SHALL indicate the [MessageResponseID](#) selected by the user. If there was no response before the [Duration](#) field of the message has elapsed, this field SHALL be null.