

## 2.9. Air Quality Cluster

This cluster provides an interface to air quality classification using distinct levels with human-readable labels.

### 2.9.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

| Revision | Description      |
|----------|------------------|
| 1        | Initial revision |

### 2.9.2. Classification

| Hierarchy | Role        | Scope    | PICS Code |
|-----------|-------------|----------|-----------|
| Base      | Application | Endpoint | AIRQUAL   |

### 2.9.3. Cluster ID

| ID     | Name        |
|--------|-------------|
| 0x005B | Air Quality |

### 2.9.4. Features

This cluster SHALL support the FeatureMap bitmap attribute as defined below.

| Bit | Code         | Feature       | Conformance | Summary                                               |
|-----|--------------|---------------|-------------|-------------------------------------------------------|
| 0   | <b>FAIR</b>  | Fair          | O           | Cluster supports the Fair air quality level           |
| 1   | <b>MOD</b>   | Moderate      | O           | Cluster supports the Moderate air quality level       |
| 2   | <b>VPOOR</b> | VeryPoor      | O           | Cluster supports the Very poor air quality level      |
| 3   | <b>XPOOR</b> | ExtremelyPoor | O           | Cluster supports the Extremely poor air quality level |