

The value of this field SHALL be greater than or equal to the value of the [MinMeasuredValue](#) field on the encompassing [MeasurementAccuracyStruct](#).

The value of this field SHALL be less than or equal to the value of the [MaxMeasuredValue](#) field on the encompassing [MeasurementAccuracyStruct](#).

2.13.5.2.1.3. PercentMax Field

This field SHALL indicate the maximum +/- percentage accuracy for the associated measurement.

2.13.5.2.1.4. PercentMin Field

This field SHALL indicate the minimum +/- percentage accuracy for the associated measurement.

2.13.5.2.1.5. PercentTypical Field

This field SHALL indicate the typical +/- percentage accuracy for the associated measurement.

2.13.5.2.1.6. FixedMax Field

This field SHALL indicate the maximum +/- fixed accuracy for the associated measurement, in the unit indicated by [MeasurementType](#).

2.13.5.2.1.7. FixedMin Field

This field SHALL indicate the minimum +/- fixed accuracy for the associated measurement, in the unit indicated by [MeasurementType](#).

2.13.5.2.1.8. FixedTypical Field

This field SHALL indicate the typical +/- fixed accuracy for the associated measurement, in the unit indicated by [MeasurementType](#).

2.13.5.2.2. MeasurementAccuracyStruct Type

This struct represents the set of accuracy ranges for a given measurement, the maximum and minimum values for the measurement, and whether the measurement is directly measured or just estimated from other information.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	MeasurementType	MeasurementTypeEnum	all				M
1	Measured	bool	all				M
2	MinMeasuredValue	int64	-2^{62} to 2^{62}				M