

2.14.5.9.3. AugmentationDuration Field

This field SHALL indicate the duration in seconds that the [TriggerDetectedDuration](#) value is to be extended by if the triggering activity is still detected during this period.

2.14.5.9.4. MaxDuration Field

This field SHALL indicate the maximum duration in seconds after the initial triggering activity detection that additional triggering activity will be detected.

2.14.5.9.5. BlindDuration Field

This field SHALL indicate the duration in seconds after a [ZoneStopped](#) event is generated that the Node SHALL NOT generate any [ZoneTriggered](#) events.

2.14.5.9.6. Sensitivity Field

This field SHALL indicate the per-zone sensitivity of the underlying zone triggering detection mechanism. The higher the value, the more sensitive the detection. The actual meaning of the values is implementation-specific.

2.14.5.10. ZoneID Type

This data type is derived from uint16.

It represents a defined Zone. This value starts at 0 and monotonically increases by 1 with each new Zone provisioned by the Node or permanently created by the device maker. A value incremented past 65534 SHALL wrap to 0. The Node SHALL verify that the incremented ID does not match any other ID. If such a match is found, the ID SHALL be incremented until a unique ID is found.

A Node SHALL only store a single Zone for a particular ZoneID and that ID SHALL NOT change over the lifetime of the Zone.

2.14.6. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	MaxUserDefinedZones	uint8	min 5	F		R V	USERDEFINED
0x0001	MaxZones	uint8	min 1	F		R V	M
0x0002	Zones	list[ZoneInformationStruct]	0 to Max-Zones	N		R V	M
0x0003	Triggers	list[ZoneTriggerControlStruct]	0 to Max-Zones	N		R V	M