

attribute indicates that there is no active schedule.

4.3.9.59. Presets Attribute

This attribute SHALL contain the current list of configured [presets](#).

On receipt of a write request:

1. If the [PresetHandle](#) field is null, the [PresetStruct](#) SHALL be treated as an added preset, and the device SHALL create a new unique value for the [PresetHandle](#) field.
 - a. If the [BuiltIn](#) field is true, a response with the status code `CONSTRAINT_ERROR` SHALL be returned.
2. If the [PresetHandle](#) field is not null, the [PresetStruct](#) SHALL be treated as a modification of an existing preset.
 - a. If the value of the [PresetHandle](#) field does not match any of the existing [presets](#), a response with the status code `NOT_FOUND` SHALL be returned.
 - b. If the value of the [PresetHandle](#) field is duplicated on multiple [presets](#) in the updated list, a response with the status code `CONSTRAINT_ERROR` SHALL be returned.
 - c. If the [BuiltIn](#) field is true, and the [PresetStruct](#) in the current value with a matching [PresetHandle](#) field has a [BuiltIn](#) field set to false, a response with the status code `CONSTRAINT_ERROR` SHALL be returned.
 - d. If the [BuiltIn](#) field is false, and the [PresetStruct](#) in the current value with a matching [PresetHandle](#) field has a [BuiltIn](#) field set to true, a response with the status code `CONSTRAINT_ERROR` SHALL be returned.
3. If the specified [PresetScenarioEnum](#) value does not exist in [PresetTypes](#), a response with the status code `CONSTRAINT_ERROR` SHALL be returned.
4. If the [Name](#) is set, but the associated [PresetTypeStruct](#) does not have the [SupportsNames](#) bit set, a response with the status code `CONSTRAINT_ERROR` SHALL be returned.
5. If appending the received [PresetStruct](#) to the pending list of Presets would cause the total number of pending [presets](#) to exceed the value of the [NumberOfPresets](#) attribute, a response with the status code `RESOURCE_EXHAUSTED` SHALL be returned.
6. If appending the received [PresetStruct](#) to the pending list of Presets would cause the total number of pending [presets](#) whose [PresetScenario](#) field matches the appended preset's [PresetScenario](#) field to exceed the value of the [NumberOfPresets](#) field on the [PresetTypeStruct](#) whose [PresetScenario](#) matches the appended preset's [PresetScenario](#) field, a response with the status code `RESOURCE_EXHAUSTED` SHALL be returned.
7. Otherwise, the write SHALL be pended until receipt of a commit request, and the status code `SUCCESS` SHALL be returned.
 - a. If the [BuiltIn](#) field is null:
 - i. If there is a [PresetStruct](#) in the current value with a matching [PresetHandle](#) field, the [BuiltIn](#) field on the pending [PresetStruct](#) SHALL be set to the value of the [BuiltIn](#) on the matching [PresetStruct](#).
 - ii. Otherwise, the [BuiltIn](#) field on the pending [PresetStruct](#) SHALL be set to false.