

On an attempt to commit, the status of this attribute SHALL be determined as follows:

1. For all existing **presets**:
 - a. If, after applying all pending changes, the updated value of the **Presets** attribute would not contain a **PresetStruct** with a matching **PresetHandle** field, indicating the removal of the **PresetStruct**, the server SHALL check for invalid removal of the **PresetStruct**:
 - i. If the **BuiltIn** field is true on the removed **PresetStruct**, the attribute status SHALL be **CONSTRAINT_ERROR**.
 - ii. If the MSCH feature is supported and the removed **PresetHandle** would be referenced by any **PresetHandle** on any **ScheduleTransitionStruct** on any **ScheduleStruct** in the updated value of the **Schedules** attribute, the attribute status SHALL be **INVALID_IN_STATE**.
 - iii. If the removed **PresetHandle** is equal to the value of the **ActivePresetHandle** attribute, the attribute status SHALL be **INVALID_IN_STATE**.
2. Otherwise, the attribute status SHALL be **SUCCESS**.

4.3.9.60. Schedules Attribute

This attribute SHALL contain a list of **ScheduleStructs**.

On receipt of a write request:

1. For all **schedules** in the write request:
 - a. If the **ScheduleHandle** field is null, the **ScheduleStruct** SHALL be treated as an added schedule, and the device SHALL create a new unique value for the **ScheduleHandle** field.
 - i. If the **BuiltIn** field is true, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - b. Otherwise, if the **ScheduleHandle** field is not null, the **ScheduleStruct** SHALL be treated as a modification of an existing schedule.
 - i. If the value of the **ScheduleHandle** field does not match any of the existing **schedules**, a response with the status code **NOT_FOUND** SHALL be returned.
 - ii. If the **BuiltIn** field is true, and the **ScheduleStruct** in the current value with a matching **ScheduleHandle** field has a **BuiltIn** field set to false, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - iii. If the **BuiltIn** field is false, and the **ScheduleStruct** in the current value with a matching **ScheduleHandle** field has a **BuiltIn** field set to true, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - c. If the specified **SystemMode** does not exist in **ScheduleTypes**, a response with the status code **CONSTRAINT_ERROR** SHALL be returned.
 - d. If the number of **transitions** exceeds the **NumberOfScheduleTransitions** value, a response with the status code **RESOURCE_EXHAUSTED** SHALL be returned.
 - e. If the value of the **NumberOfScheduleTransitionPerDay** attribute is not null, and the number of **transitions** on any single day of the week exceeds the **NumberOfScheduleTransitionPerDay** value, a response with the status code **RESOURCE_EXHAUSTED** SHALL be returned.