

Each setpoint transition will begin with the day of week for this transition. There can be up to 10 transitions for each command.

4.3.10.2.3. ModeForSequence Field

This field SHALL indicate how the application decodes the setpoint fields of each transition in the Transitions list.

If the HeatSetpointPresent bit is On, the HeatSetpoint field SHALL NOT be null in **every** entry of the Transitions list.

If the HeatSetpointPresent bit is Off, the HeatSetpoint field SHALL be null in **every** entry of the Transitions list.

If the CoolSetpointPresent bit is On, the CoolSetpoint field SHALL NOT be null in **every** entry of the Transitions list.

If the CoolSetpointPresent bit is Off, the CoolSetpoint field SHALL be null in **every** entry of the Transitions list.

At least one of the bits in the Mode For Sequence byte SHALL be on.

Both bits must be respected, even if the HEAT or COOL feature is not supported, to ensure the command is decoded and handled correctly.

4.3.10.2.4. Transitions Field

This field SHALL contain the list of setpoint transitions used to update the specified daily schedules

4.3.10.2.5. Effect on Receipt

Upon receipt, the weekly schedule for updating setpoints SHALL be stored in the thermostat and SHOULD begin at the time of receipt. A status code SHALL be sent in response.

When a command is received that requires a total number of transitions greater than the device supports, the status of the response SHALL be INSUFFICIENT_SPACE.

When any of the setpoints sent in the sequence is out of range (AbsMin/MaxSetPointLimit), or when the Mode for Sequence field includes a mode not supported by the device, the status of the response SHALL be CONSTRAINT_ERROR and no setpoints from the entire sequence SHOULD be used.

When an overlapping transition is detected, the status of the response SHALL be FAILURE.

When a device which does not support multiple days in a command receives a command with more than one bit set in the DayOfWeekForSequence field, or when a device which does not support multiple modes in a command receives a command with more than one bit set in the ModeForSequence field, or when the contents of the Transitions field does not agree with NumberOfTransitionsForSequence, DayOfWeekForSequence or ModeForSequence, the status of the response SHALL be INVALID_COMMAND.

When the transitions could be added successfully, the status of the response SHALL be SUCCESS.