

command retracts the bolt without pulling the latch. The Unlock Door command fully unlocks the door by retracting the bolt and briefly pulling the latch. While the latch is pulled, the lock state changes to Unlatched. Locks without unbolting support don't differentiate between unbolting and unlocking and perform the same operation for both commands.

5.2.4.12. AliroProvisioning Feature

Locks that support this feature implement the Aliro specification as defined in [\[Aliro\]](#) and support Matter as a method for provisioning Aliro credentials.

5.2.4.13. AliroBLEUWB Feature

Locks that support this feature implement the Bluetooth LE + UWB Access Control Flow as defined in [\[Aliro\]](#).

5.2.5. Recommended steps for creating a new User

It is RECOMMENDED that the Administrator query the door lock for what users already exist in its database to find an available UserIndex for creating a new User (see [Section 5.2.10.33, “GetUser Command”](#)).

1. Use [SetUser](#) command with an available UserIndex to set the user record fields as applicable.
2. Use [SetCredential](#) command with same UserIndex to add one or more credentials as applicable.
3. Use [SetWeekDaySchedule](#) command or [SetYearDaySchedule](#) command with same UserIndex to add one or more schedule restrictions as applicable.

5.2.6. Data Types

5.2.6.1. DaysMaskBitmap Type

This data type is derived from map8.

This bitmap SHALL indicate the days of the week the Week Day schedule applies for.

Bit	Name	Summary	Conformance
0	Sunday	Schedule is applied on Sunday	M
1	Monday	Schedule is applied on Monday	M
2	Tuesday	Schedule is applied on Tuesday	M
3	Wednesday	Schedule is applied on Wednesday	M
4	Thursday	Schedule is applied on Thursday	M