

Value	Name	Summary	Conformance
2	RFID	RFID identifier credential type	RID
3	Fingerprint	Fingerprint identifier credential type	FGP
4	FingerVein	Finger vein identifier credential type	FGP
5	Face	Face identifier credential type	FACE
6	AliroCredentialIssuerKey	A Credential Issuer public key as defined in Aliro	ALIRO
7	AliroEvictableEndpointKey	An Endpoint public key as defined in Aliro which can be evicted if space is needed for another endpoint key	ALIRO
8	AliroNonEvictableEndpointKey	An Endpoint public key as defined in Aliro which cannot be evicted if space is needed for another endpoint key	ALIRO

5.2.6.9.1. AliroCredentialIssuerKey Value

Credentials of this type SHALL be 65-byte uncompressed elliptic curve public keys as defined in section 2.3.3 of [SEC 1](#).

Credentials of this type SHALL NOT be used to allow operating the lock. They SHALL be used, as defined in [\[Aliro\]](#), to create new credentials of type [AliroEvictableEndpointKey](#) via a step-up transaction.

When performing the step-up transaction, the lock SHALL request the data element with identifier "matter1", and SHALL attempt to create a new credential of type [AliroEvictableEndpointKey](#) if and only if the data element is returned and the Access Credential can be validated using the AliroCredentialIssuerKey.

When a new credential of type AliroEvictableEndpointKey is added in this manner, it SHALL be associated with the same user record as the AliroCredentialIssuerKey credential that allowed the new credential to be added.

If there are no available credential slots to add a new AliroEvictableEndpointKey credential (i.e. either the NumberOfCredentialsSupportedPerUser or the NumberOfAliroEndpointKeysSupported limit has been reached) but there exist credentials of type AliroEvictableEndpointKey associated with the user record, the server SHALL remove one of those credentials using the same procedure