

5.2.7.1. StatusCodeEnum Type

This data type is derived from enum8.

Value	Name	Summary	Conformance
0x02	DUPLICATE	Entry would cause a duplicate credential/ID.	M
0x03	OCCUPIED	Entry would replace an occupied slot.	M

5.2.7.2. DUPLICATE Code

The provided User ID, PIN or RFID code or other credential is a duplicate of an existing entry.

5.2.7.3. OCCUPIED Code

The provided User ID, Credential ID, or entry location is already occupied. The entry might need to be deleted or a different ID or location chosen.

5.2.8. PIN/RFID Code Format

The PIN/RFID codes defined in this specification are all octet strings.

All value in the PIN/RFID code SHALL be ASCII encoded regardless if the PIN/RFID codes are number or characters. For example, code of “1, 2, 3, 4” SHALL be represented as 0x31, 0x32, 0x33, 0x34.

5.2.9. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	LockState	LockStateEnum	desc	P X		R V	M
0x0001	LockType	LockTypeEnum	desc			R V	M
0x0002	ActuatorEnabled	bool	all			R V	M
0x0003	DoorState	DoorStateEnum	desc	P X		R V	DPS
0x0004	DoorOpen Events	uint32	all			RW VM	[DPS]
0x0005	Door-Closed Events	uint32	all			RW VM	[DPS]