

5.2.9.36. ExpiringUserTimeout Attribute

This attribute SHALL indicate the number of minutes a PIN, RFID, Fingerprint, or other credential associated with a user of type ExpiringUser SHALL remain valid after its first use before expiring. When the credential expires the UserStatus for the corresponding user record SHALL be set to OccupiedDisabled.

Alarm Code Value	AlarmMaskBitmap Bit
0	0
1	1
2	2
3	3
4	4
5	5
6	6

5.2.9.37. AliroReaderVerificationKey Attribute

This attribute SHALL indicate the verification key component of the Reader's key pair as defined in [\[Aliro\]](#). The value, if not null, SHALL be an uncompressed elliptic curve public key as defined in section 2.3.3 of [SEC 1](#).

This attribute SHALL be null if no Reader key pair has been configured on the lock. See [Section 5.2.10.42, "SetAliroReaderConfig Command"](#).

5.2.9.38. AliroReaderGroupIdentifier Attribute

This attribute SHALL indicate the reader_group_identifier as defined in [\[Aliro\]](#).

This attribute SHALL be null if no reader_group_identifier has been configured on the lock. See [Section 5.2.10.42, "SetAliroReaderConfig Command"](#).

5.2.9.39. AliroReaderGroupSubIdentifier Attribute

This attribute SHALL indicate the reader_group_sub_identifier as defined in [\[Aliro\]](#).

5.2.9.40. AliroExpeditedTransactionSupportedProtocolVersions Attribute

This attribute SHALL indicate the list of protocol versions supported for expedited transactions as defined in [\[Aliro\]](#).

5.2.9.41. AliroGroupResolvingKey Attribute

This attribute SHALL indicate the Group Resolving Key as defined in [\[Aliro\]](#).

This attribute SHALL be null if no group resolving key has been configured on the lock. See [Section 5.2.10.42, "SetAliroReaderConfig Command"](#).