

5.2.10.18. GetYearDayScheduleResponse Command

Returns the year day schedule data for the specified schedule and user indexes.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	YearDayIndex	uint8	1 to NumberOfYearDaySchedulesSupportedPerUser			M
1	UserIndex	uint16	1 to NumberOfTotalUsersSupported			M
2	Status	enum8	desc			M
3	LocalStartTime	epoch-s	all			O
4	LocalEndTime	epoch-s	all			O

5.2.10.18.1. YearDayIndex Field

This field SHALL indicate the index of the Year Day schedule.

5.2.10.18.2. UserIndex Field

This field SHALL indicate the user ID.

5.2.10.18.3. Status Field

Status SHALL be one of the following values:

- SUCCESS if both YearDayIndex and UserIndex are valid and there is a corresponding schedule entry.
- INVALID_COMMAND if either YearDayIndex and/or UserIndex values are not within valid range
- NOT_FOUND if no corresponding schedule entry found for YearDayIndex.
- NOT_FOUND if no corresponding user entry found for UserIndex.

If this field is SUCCESS, the optional fields for this command SHALL be present. For other (error) status values, only the fields up to the status field SHALL be present.

5.2.10.18.4. LocalStartTime Field

This field SHALL indicate the starting time for the Year Day schedule in Epoch Time in Seconds with local time offset based on the local timezone and DST offset on the day represented by the value. This SHALL be null if the schedule is not set for the YearDayIndex and UserIndex provided.