

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	HolidayIndex	uint8	1 to NumberOfHolidaySchedulesSupported			M
1	LocalStartTime	epoch-s	all			M
2	LocalEndTime	epoch-s	all			M
3	OperatingMode	OperatingModeEnum	all			M

Return status SHALL be one of the following values:

Name	Summary
SUCCESS	Setting Holiday schedule was successful.
FAILURE	Some unexpected internal error occurred setting Holiday schedule.
INVALID_COMMAND	One or more fields violates constraints or is invalid.

5.2.10.20.1. HolidayIndex Field

This field SHALL indicate the index of the Holiday schedule.

5.2.10.20.2. LocalStartTime Field

This field SHALL indicate the starting time for the Holiday Day schedule in Epoch Time in Seconds with local time offset based on the local timezone and DST offset on the day represented by the value.

5.2.10.20.3. LocalEndTime Field

This field SHALL indicate the ending time for the Holiday Day schedule in Epoch Time in Seconds with local time offset based on the local timezone and DST offset on the day represented by the value. LocalEndTime SHALL be greater than LocalStartTime.

5.2.10.20.4. OperatingMode Field

This field SHALL indicate the operating mode to use during this Holiday schedule start/end time.

5.2.10.21. GetHolidaySchedule Command

Get the holiday schedule for the specified index.