

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	HolidayIndex	uint8	1 to NumberOfHolidaySchedulesSupported			M

5.2.10.22. GetHolidayScheduleResponse Command

Returns the Holiday Schedule Entry for the specified Holiday ID.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	HolidayIndex	uint8	1 to NumberOfHolidaySchedulesSupported			M
1	Status	enum8	desc			M
2	LocalStartTime	epoch-s	all	X		O
3	Local End Time	epoch-s	all	X		O
4	Operating-Mode	Operating-ModeEnum	all	X		O

5.2.10.22.1. HolidayIndex Field

This field SHALL indicate the index of the Holiday schedule.

5.2.10.22.2. Status Field

Status SHALL be one of the following values:

- FAILURE if the attribute NumberOfHolidaySchedulesSupported is zero.
- SUCCESS if the HolidayIndex is valid and there is a corresponding schedule entry.
- INVALID_COMMAND if the HolidayIndex is not within valid range
- NOT_FOUND if the HolidayIndex is within the valid range, however, there is not corresponding schedule entry found.

If this field is SUCCESS, the optional fields for this command SHALL be present. For other (error) status values, only the fields up to the status field SHALL be present.

5.2.10.22.3. LocalStartTime Field

This field SHALL indicate the starting time for the Holiday schedule in Epoch Time in Seconds with local time offset based on the local timezone and DST offset on the day represented by the value.