

This SHALL be null if the schedule is not set for the HolidayIndex provided.

5.2.10.22.4. LocalEndTime Field

This field SHALL indicate the ending time for the Holiday schedule in Epoch Time in Seconds with local time offset based on the local timezone and DST offset on the day represented by the value. LocalEndTime SHALL be greater than LocalStartTime. This SHALL be null if the schedule is not set for the HolidayIndex provided.

5.2.10.22.5. OperatingMode Field

This field SHALL indicate the operating mode to use during this Holiday schedule start/end time. This SHALL be null if the schedule is not set for the HolidayIndex provided.

5.2.10.23. ClearHolidaySchedule Command

Clears the holiday schedule or all holiday schedules.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	HolidayIndex	uint8	1 to NumberOfHolidaySchedulesSupported, 0xFE			M

5.2.10.23.1. HolidayIndex Field

This field SHALL indicate the Holiday schedule index to clear or 0xFE to clear all Holiday schedules.

5.2.10.24. SetUserType Command

Set the user type for a specified user.

For user type value please refer to User Type Value.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	UserID	uint16	desc			M
1	UserType	UserType-Enum	all			M

Return status SHALL be one of the following values:

Name	Summary
SUCCESS	Setting User Type was successful.
FAILURE	Some unexpected internal error occurred setting User Type.