

5.2.11.5. LockUserChange Event

The door lock server sends out a LockUserChange event when a lock user, schedule, or credential change has occurred.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Lock-Data- Type	Lock-Data- Type- Enum	all			M
1	Data- Operation- Type	Data- Operation- Type- Enum	all			M
2	Operation- Source	Operation- Source- Enum	Aliro, Unspecified, Keypad, Remote			M
3	User- Index	uint16	all	X		M
4	Fabric- Index	fabric-idx	all	X		M
5	Source- Node	node-id	all	X		M
6	Data- Index	uint16	all	X		M

5.2.11.5.1. LockDataType Field

This field SHALL indicate the lock data type that was changed.

5.2.11.5.2. DataOperationType Field

This field SHALL indicate the data operation performed on the lock data type changed.

5.2.11.5.3. OperationSource Field

This field SHALL indicate the source of the user data change.

5.2.11.5.4. UserIndex Field

This field SHALL indicate the lock UserIndex associated with the change (if any). This SHALL be null if there is no specific user associated with the data operation. This SHALL be 0xFFFF if all users are affected (e.g. Clear Users).

5.2.11.5.5. FabricIndex Field

This field SHALL indicate the fabric index of the fabric that performed the change (if any). This SHALL be null if there is no fabric that can be determined to have caused the change. This SHALL NOT be null if the operation source is "Remote".