

5.2.11.5.6. SourceNode Field

This field SHALL indicate the Node ID that performed the change (if any). The Node ID of the node that performed the change. This SHALL be null if there was no Node involved in the change. This SHALL NOT be null if the operation source is "Remote".

5.2.11.5.7. DataIndex Field

This field SHALL indicate the index of the specific item that was changed (e.g. schedule, PIN, RFID, etc.) in the list of items identified by LockDataType. This SHALL be null if the LockDataType does not correspond to a list that can be indexed into (e.g. ProgrammingUser). This SHALL be 0xFFFE if all indices are affected (e.g. ClearPINCode, ClearRFIDCode, ClearWeekDaySchedule, ClearYear-DaySchedule, etc.).

5.3. Window Covering Cluster

The window covering cluster provides an interface for controlling and adjusting automatic window coverings such as drapery motors, automatic shades, curtains and blinds.

5.3.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Mandatory global ClusterRevision attribute added; CCB 1994 1995 1996 1997 2086 2094 2095 2096 2097
2	CCB 2328
3	CCB 2477 2555 2845 3028
4	All Hubs changes with FeatureMap & OperationalStatus attribute
5	New data model format and notation. Created plus clarified PositionAware and AbsolutePosition features. General cleanup of functionality.
6	Marked AbsolutePosition feature and associated elements provisional.
7	Removed ABS feature and all associated elements from the cluster since it is disallowed by the Window Covering Device Type.

5.3.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	WNCV