

Bit	Code	Feature	Conformance	Summary
8	MO	ManuallyOperable	O	Supports the manual operation feature

5.4.5.1. Positioning Feature

This feature SHALL indicate that the closure can be set to discrete positions, including at minimum the FullyOpen and FullyClosed positions.

5.4.5.2. MotionLatching Feature

This feature SHALL indicate that the closure can be latched and unlatched. When latched, the feature secures an axis, preventing associated actuators from moving components along that axis.

5.4.5.3. Instantaneous Feature

This feature SHALL indicate that the closure is capable of changing its position or state instantaneously. As a result, the Speed feature is not applicable, and the [Stop](#) command is not usable. In such closures, the OverallCurrentState attribute SHALL immediately follow the OverallTargetState attribute. The state transition diagram remains applicable, however, transitions involving the Stop state SHALL be omitted.

5.4.5.4. Speed Feature

This feature SHALL indicate that the closure supports configurable speed during motion toward a target position. The feature uses the values in ThreeLevelAutoEnum to set the supported speed levels.

5.4.5.4.1. Low Value

This setting prioritizes quiet operation and is typically used in silent mode. It minimizes noise from the closure product, making it ideal for environments where discretion or minimal disturbance is important, such as during nighttime operation or in quiet settings.

5.4.5.4.2. Medium Value

The most commonly used speed for everyday use. It offers a balanced performance with reliable operation and moderate noise levels, suitable for general tasks in typical working conditions.

5.4.5.4.3. High Value

Designed for time-critical situations, this setting allows the closure to open or close as quickly as possible. It prioritizes speed over noise or smoothness, ensuring rapid response when urgent access or sealing is needed.

5.4.5.4.4. Auto Value

In auto the speed of the movement is entirely determined by the closure. The behavior when using this value is manufacturer specific.