

NOTE

The server might not support three different speed values. The meaning of Low, Medium and High speeds is manufacturer-specific, as long as **Low <= Medium <= High** in terms of actual speed of motion. The Speed Feature requires at least two distinct speeds to be supported.

5.4.5.5. Ventilation Feature

This feature SHALL indicate that the closure can be set to a designated Ventilation position (e.g., partially open).

5.4.5.6. Pedestrian Feature

This feature SHALL indicate that the closure can be set to a dedicated Pedestrian position. The Pedestrian position provides a clear walkway through the closure.

5.4.5.7. Calibration Feature

This feature SHALL indicate the capability to trigger a calibration procedure. The calibration can either be fully automated, or require manual steps not described in this specification.

5.4.5.8. Protection Feature

This feature SHALL indicate that the closure is capable of activating a form of protection, such as protection against wind. A protection is manufacturer-specific, and it could be a simple software limitation, or a mechanical system deployed by the closure.

5.4.5.9. ManuallyOperable Feature

This feature SHALL indicate that the closure can be operated manually by a user, such as to open a window.

5.4.6. Data Types**5.4.6.1. CurrentPositionEnum Type**

This data type is derived from enum8.

Value	Name	Summary	Conformance
0	FullyClosed	Fully closed state	M
1	FullyOpened	Fully opened state	M
2	PartiallyOpened	Partially opened state (closure is not fully opened or fully closed)	M
3	OpenedForPedestrian	Closure is in the Pedestrian position	PD
4	OpenedForVentilation	Closure is in the Ventilation position	VT