

- null if the closure's current secure state is unknown.

This field provides no additional details regarding mechanical properties of the closure mechanism. It is intended only as supplementary information and not as a replacement for a comprehensive security system. It is primarily useful for closures on the outer shell of objects, such as garage doors, windows, or doors.

5.4.6.6. OverallTargetStateStruct Type

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Position	TargetPositionEnum	all	X	null		PS
1	Latch	bool	all	X	null		LT
2	Speed	ThreeLevelAutoEnum	all		MS		SP

5.4.6.6.1. Position field

This field SHALL indicate the target position that the closure is moving to. It SHALL be null if there is no target position.

5.4.6.6.2. Latch field

This field SHALL indicate the desired latching state of the closure. It SHALL be null if there is no desired latching state.

5.4.6.6.3. Speed field

This field SHALL indicate the desired speed at which the closure should perform the movement toward the target position. If no speed value has yet been set, the server SHALL select and set one of the speed values defined in the ThreeLevelAutoEnum.

5.4.6.7. LatchControlModesBitmap Type

This data type is derived from map8.

Bit	Name	Summary	Conformance
0	RemoteLatching	Remote latching capability	LT
1	RemoteUnlatching	Remote unlatching capability	LT

5.4.6.7.1. RemoteLatching Bit

This bit SHALL indicate whether the latch supports remote latching or not:

- 0 = the latch can only be latched through manual, physical operation.