

blind.

5.4.9.3. EngageStateChanged Event

This event, if supported, SHALL be generated when the MainStateEnum attribute changes state to and from disengaged, indicating if the actuator is Engaged or Disengaged.

This event SHALL contain the following fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	EngageValue	bool	all			M

- *True*, when the actuator is in a Engaged state, actuator movements possible.
- *False*, when the actuator is in a Disengaged state, preventing any actuator movements.

5.4.9.4. SecureStateChanged Event

This event, if supported, SHALL be generated when the SecureState field in the OverallCurrentState attribute changes. It is used to indicate whether a closure is securing a space against possible unauthorized entry.

This event SHALL contain the following fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	SecureValue	bool	all			M

- *True*, when the closure is in a secure state, e.g. unauthorized/undetectable access is not possible.
- *False*, when the closure is in an insecure state, e.g. unauthorized/undetectable access is possible.

5.5. Closure Dimension Cluster

This cluster provides an interface for controlling a single degree of freedom (also referred to as a "dimension" or an "axis" below) of a composed closure. This could be a degree of freedom in a 6-axis framework for the overall closure or a panel in the closure, or some other degree of freedom.

An instance of this cluster may represent position along a single axis, as specified by the FeatureMap, which can be one of:

- Translation : panel translates along one axis
- Rotation : panel rotates around an axis of rotation
- Modulation : panel modifies its aspect to modulate a flow

This cluster may also be used to latch or anchor a panel in a position, if the panel supports that.