

5.5.5.5. Speed Feature

This feature SHALL indicate that the closure dimension can be driven at different speed levels: Low, Medium, and High. Please refer to [Section 5.4.5.4, “Speed Feature”](#) for more details.

NOTE

The server might not support three different speed values. The manufacturer SHALL select speed values linked to Low, Medium and High such that **Low <= Medium <= High**.

5.5.5.6. Translation Feature

This feature SHALL indicate that the panel can move along a single axis. The possible directions include downward, upward, leftward, rightward, forward, and backward. The Translation feature is used to control the position of the panel along the specified axis.

5.5.5.7. Rotation Feature

This feature SHALL indicate that the panel can rotate around a single axis. The possible axes include left, right, top, bottom, centered vertical, and centered horizontal. The Rotation feature is used to control the orientation of the panel around the specified axis.

5.5.5.8. Modulation Feature

This feature SHALL indicate that the panel can modify its aspect to control a particular flow, such as light, air, or privacy. The possible modulation types include slats orientation, slats openwork, stripes alignment, opacity, and ventilation. The Modulation feature is used to adjust the panel's properties to achieve the desired effect.

5.5.6. Data Types

5.5.6.1. TranslationDirectionEnum Type

This data type is derived from enum8.

Value	Name	Summary	Conformance
0	Downward	Downward translation	M
1	Upward	Upward translation	M
2	VerticalMask	Vertical mask translation	M
3	VerticalSymmetry	Vertical symmetry translation	M
4	Leftward	Leftward translation	M
5	Rightward	Rightward translation	M
6	HorizontalMask	Horizontal mask translation	M