

6.2.5. Events

ID	Name	Priority	Access	Conformance
0	LoggedOut	CRITICAL	A S	O

6.2.5.1. LoggedOut Event

This event can be used by the Content App to indicate that the current user has logged out. In response to this event, the Fabric Admin SHALL remove access to this Content App by the specified Node. If no Node is provided, then the Fabric Admin SHALL remove access to all non-Admin Nodes.

The data of this event SHALL contain the following information:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Node	node-id	all			O

6.2.5.1.1. Node

This field SHALL provide the Node ID corresponding to the user account that has logged out, if that Node ID is available. If it is NOT available, this field SHALL NOT be present in the event.

6.3. Application Basic Cluster

This cluster provides information about a Content App running on a Video Player device which is represented as an endpoint (see Device Type Library document).

The cluster server for this cluster should be supported on each endpoint that represents a Content App on a Video Player device. This cluster provides identification information about the Content App such as vendor and product.

6.3.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

6.3.2. Classification

Hierarchy	Role	Scope	PICS Code
Base	Application	Endpoint	APBSC