

6.4.6.1. CatalogList Attribute

This attribute SHALL specify the list of supported application catalogs, where each entry in the list is the Connectivity Standards Alliance-issued vendor ID for the catalog. The DIAL registry (see [\[DIAL Registry\]](#)) SHALL use value 0x0000.

It is expected that Content App Platform providers will have their own catalog vendor ID (set to their own Vendor ID) and will assign an ApplicationID to each Content App.

6.4.6.2. CurrentApp Attribute

This attribute SHALL specify the current in-focus application, identified using an Application ID, catalog vendor ID and the corresponding endpoint number when the application is represented by a Content App endpoint. A null SHALL be used to indicate there is no current in-focus application.

6.4.7. Commands

ID	Name	Direction	Response	Access	Conformance
0x00	LaunchApp	client ⇒ server	LauncherResponse	O	M
0x01	StopApp	client ⇒ server	LauncherResponse	O	M
0x02	HideApp	client ⇒ server	LauncherResponse	O	M
0x03	LauncherResponse	client ⇐ server	N		M

6.4.7.1. LaunchApp Command

Upon receipt of this command, the server SHALL launch the application with optional data. The application SHALL be either

- the specified application, if the Application Platform feature is supported;
- otherwise the application corresponding to the endpoint.

The endpoint SHALL launch and bring to foreground the requisite application if the application is not already launched and in foreground. The Status attribute SHALL be updated to ActiveVisibleFocus on the Application Basic cluster of the Endpoint corresponding to the launched application. The Status attribute SHALL be updated on any other application whose Status MAY have changed as a result of this command. The CurrentApp attribute, if supported, SHALL be updated to reflect the new application in the foreground.

This command returns a Launcher Response.