

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ProgramIdentifier	string	max 255			M
1	ShouldRecordSeries	bool				M
2	ExternalIDList	list[AdditionalInfoStruct]	max 255		empty	O
3	Data	octstr	max 8092		MS	O

6.6.7.7.1. ProgramIdentifier Field

This field SHALL indicate the program identifier for the program that should be recorded. This value is provided by the identifier field in [ProgramStruct](#).

6.6.7.7.2. ShouldRecordSeries Field

This field SHALL indicate whether the whole series associated to the program should be recorded. For example, invoking record program on an episode with that flag set to true, the target should schedule record the whole series.

6.6.7.7.3. ExternalIDList Field

This field, if present, SHALL indicate the list of additional external content identifiers.

6.6.7.7.4. Data Field

This field, if present, SHALL indicate app-specific data.

6.6.7.8. CancelRecordProgram Command

Cancel recording for a specific program or series.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ProgramIdentifier	string	max 255			M
1	ShouldRecordSeries	bool				M
2	ExternalIDList	list[AdditionalInfoStruct]	max 255		empty	O
3	Data	octstr	max 8092		MS	O