

6.7.5.10.5. Splash Field

This field SHALL indicate the screen shown when the Video Player is in an idle state. If this property is not populated, the Video Player SHALL default to logo or the provider name.

6.7.5.10.6. Watermark Field

This field SHALL indicate watermark shown when the media is playing.

6.7.5.11. PlaybackPreferencesStruct Type

PlaybackPreferencesStruct defines the preferences sent by the client to the receiver in the Content-Launcher LaunchURL or LaunchContent commands.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Playback-Position	uint64		X			AS
1	TextTrack	TrackPreferenceStruct		X			TT
2	Audio-Tracks	list[TrackPreferenceStruct]		X			AT

6.7.5.11.1. PlaybackPosition Field

This field SHALL indicate the preferred position (in milliseconds) in the media to launch playback from. In case the position falls in the middle of a frame, the server SHALL set the position to the beginning of that frame and set the **SampledPosition** attribute on the MediaPlayer cluster accordingly. A value of null SHALL indicate that playback position is not applicable for the current state of the media playback. (For example : Live media with no known duration and where seek is not supported).

6.7.5.11.2. TextTrack Field

This field SHALL indicate the user's preferred Text Track. A value of null SHALL indicate that the user did not specify a preferred Text Track on the client. In such a case, the decision to display and select a Text Track is up to the server.

6.7.5.11.3. AudioTracks Field

This field SHALL indicate the list of the user's preferred Audio Tracks. If the list contains multiple values, each AudioTrack must also specify a unique audioOutputIndex to play the track on. A value of null SHALL indicate that the user did not specify a preferred Audio Track on the client. In such a case, the decision to play and select an Audio Track is up to the server.