

6.11.5. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	TargetList	list[TargetInfoStruct]				R V	M
0x0001	Current-Target	uint8	desc		0xFF	R V	O

6.11.5.1. TargetList Attribute

This attribute SHALL represent a list of targets that can be navigated to within the experience presented to the user by the Endpoint (Video Player or Content App). The list SHALL NOT contain any entries with the same Identifier in the TargetInfoStruct object.

6.11.5.2. CurrentTarget Attribute

This attribute SHALL represent the Identifier for the target which is currently in foreground on the corresponding Endpoint (Video Player or Content App), or 0xFF to indicate that no target is in the foreground.

When not 0xFF, the CurrentTarget SHALL be an Identifier value contained within one of the TargetInfoStruct objects in the TargetList attribute.

6.11.6. Commands

ID	Name	Direction	Response	Access	Conformance
0x00	NavigateTarget	client ⇒ server	NavigateTargetResponse	O	M
0x01	NavigateTargetResponse	client ⇐ server	N		M

6.11.6.1. NavigateTarget Command

Upon receipt, this SHALL navigation the UX to the target identified.

ID	Field	Type	Constraint	Quality	Fallback	Conformance
0	Target	uint8	all			M
1	Data	string			MS	O

6.11.6.1.1. Target Field

This field SHALL indicate the Identifier for the target for UX navigation. The Target SHALL be an Identifier value contained within one of the TargetInfoStruct objects in the TargetList attribute.