

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Data	string	max 500			M
1	EncodingHint	string	max 100			O

6.12.5.1.1. Data Field

This field SHALL indicate content app-specific data.

6.12.5.1.2. EncodingHint Field

This optional field SHALL indicate a content app-specific hint to the encoding of the data.

6.12.5.2. ContentAppMessageResponse Command

This command SHALL be generated in response to ContentAppMessage command.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	Status	StatusEnum	all			M
1	Data	string	max 500			O
2	EncodingHint	string	max 100			O

6.12.5.2.1. Status Field

This field SHALL indicate the status of the command which resulted in this response.

6.12.5.2.2. Data Field

This optional field SHALL indicate content app-specific data.

6.12.5.2.3. EncodingHint Field

This optional field SHALL indicate a content app-specific hint to the encoding of the data.

6.13. Content Control Cluster

This cluster is used for managing the content control (including "parental control") settings on a media device such as a TV, or Set-top Box.

This cluster allows to configure content control settings by clients with the Management privilege. It is responsibility of the end product to enforce appropriate right access (for example, to prevent a child from disabling this feature).

NOTE Support for Content Control cluster is provisional.