

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0009	BlockApplicationList	list[AppInfoStruct]	all			R V	BA
0x000A	BlockContentTimeWindow	list[TimeWindowStruct]	max 7			R V	BTW

6.13.7.1. Enabled Attribute

This attribute SHALL indicate whether the Content Control feature implemented on a media device is turned off (FALSE) or turned on (TRUE).

6.13.7.2. OnDemandRatings Attribute

This attribute SHALL provide the collection of ratings that are currently valid for this media device. The items should honor the metadata of the on-demand content (e.g. Movie) rating system for one country or region where the media device has been provisioned. For example, for the MPAA system, RatingName may be one value out of "G", "PG", "PG-13", "R", "NC-17".

The media device SHALL have a way to determine which rating system applies for the on-demand content and then populate this attribute. For example, it can do it through examining the Location attribute in the Basic Information cluster, and then determining which rating system applies.

The ratings in this collection SHALL be in order from a rating for the youngest viewers to the one for the oldest viewers. Each rating in the list SHALL be unique.

6.13.7.3. OnDemandRatingThreshold Attribute

This attribute SHALL indicate a threshold rating as a content filter which is compared with the rating for on-demand content. For example, if the on-demand content rating is greater than or equal to OnDemandRatingThreshold, for a rating system that is ordered from lower viewer age to higher viewer age, then on-demand content is not appropriate for the User and the Node SHALL prevent the playback of content.

This attribute SHALL be set to one of the values present in the OnDemandRatings attribute.

When this attribute changes, the device SHOULD make the user aware of any limits of this feature. For example, if the feature does not control content within apps, then the device should make this clear to the user when the attribute changes.

6.13.7.4. ScheduledContentRatings Attribute

This attribute SHALL indicate a collection of ratings which ScheduledContentRatingThreshold can be set to. The items should honor metadata of the scheduled content rating system for the country or region where the media device has been provisioned.