

The media device SHALL have a way to determine which scheduled content rating system applies and then populate this attribute. For example, this can be done by examining the Location attribute in Basic Information cluster, and then determining which rating system applies.

The ratings in this collection SHALL be in order from a rating for the youngest viewers to the one for the oldest viewers. Each rating in the list SHALL be unique.

6.13.7.5. ScheduledContentRatingThreshold Attribute

This attribute SHALL indicate a threshold rating as a content filter which is used to compare with the rating for scheduled content. For example, if the scheduled content rating is greater than or equal to ScheduledContentRatingThreshold for a rating system that is ordered from lower viewer age to higher viewer age, then the scheduled content is not appropriate for the User and SHALL be blocked.

This attribute SHALL be set to one of the values present in the ScheduledContentRatings attribute.

When this attribute changes, the device SHOULD make the user aware of any limits of this feature. For example, if the feature does not control content within apps, then the device should make this clear to the user when the attribute changes.

6.13.7.6. ScreenDailyTime Attribute

This attribute SHALL indicate the amount of time (in seconds) which the User is allowed to spend watching TV within one day when the Content Control feature is activated.

6.13.7.7. RemainingScreenTime Attribute

This attribute SHALL indicate the remaining screen time (in seconds) which the User is allowed to spend watching TV for the current day when the Content Control feature is activated. When this value equals 0, the media device SHALL terminate the playback of content.

This attribute SHALL be updated when the AddBonusTime command is received and processed successfully (with the correct PIN).

6.13.7.8. BlockUnrated Attribute

This attribute SHALL indicate whether the playback of unrated content is allowed when the Content Control feature is activated. If this attribute equals FALSE, then playback of unrated content SHALL be permitted. Otherwise, the media device SHALL prevent the playback of unrated content.

When this attribute changes, the device SHOULD make the user aware of any limits of this feature. For example, if the feature does not control content within apps, then the device should make this clear to the user when the attribute changes.

6.13.7.9. BlockChannelList Attribute

This attribute SHALL indicate a set of channels that SHALL be blocked when the Content Control feature is activated.